


H11

SUMMER-HP

The specially formulated compounds are
ECO FRIENDLY,
highly fuel efficient and long lasting.

**Shoulder Designed**

The closed shoulder design strengthens shoulder blocks for superior handling performance.

**Wet Performance**

The three wide tread grooves and wave-like sipes efficiently drain water to improve grip on wet roads and improve driving safety.

**Handling**

A pair of center ribs and the solid shoulder blocks maintain stable contact with the road to ensure great handling.




PN	SIZE	PB	L	SR	SL OR NOT	SD/WALL	TD (mm)	STANDARD PNM	SW (mm)	OD. (mm)	UTQG	MAXLOAD (kg)	PRESSURE (kpa)
13	145/70R13	/	75	T	/	R5M	7.0	4.508	156	514	360/3/A	345	380
	145/80R13	/	75	T	/	R5M	7.0	4.508	145	562	360/3/A	381	390
	155/65R13	/	73	T	/	R5M	7.3	4.508	157	532	360/3/A	365	390
	165/60R13	/	75	T	/	R5M	7.0	5.008	167	518	360/3/A	387	390
	165/60R13	/	75	T	/	R5M	7.0	4.508	187	518	360/3/A	487	390
	165/65R13	/	77	T	/	R5M	7.2	5.008	170	544	360/3/A	412	390
	165/70R13	/	79	T	/	R5M	7.2	5.008	170	562	360/3/A	427	390
	165/70R13	/	83	T	SL	R5M	7.2	5.508	170	562	360/3/A	487	390
	165/70R13	/	83	T	/	R5M	7.2	4.508	168	594	360/3/A	487	390
	175/70R13	/	82	T	/	R5M	7.2	4.508	177	516	360/3/A	475	390
	175/70R13	/	82	T	/	RW1	7.2	5.008	177	516	360/3/A	475	390
	185/70R13	/	86	T	/	R5M	7.4	5.1/2/J	188	596	360/3/A	510	390
	185/70R13	/	86	T	/	RW1	7.4	5.1/2/J	188	596	360/3/A	510	390
14	155/65R14	/	75	T	/	R5M	7.0	6J	157	528	360/3/A	387	390
	165/60R14	/	75	W	/	R5M	7.2	4.1/2/J	159	534	360/3/A	387	390
	165/65R14	/	79	T	/	R5M	7.2	5J	170	518	360/3/A	457	390
	165/70R14	/	85	T	SL	R5M	7.2	5J	170	548	360/3/A	515	390
	165/70R14	/	81	T	/	R5M	7.2	5.1/2/J	170	548	360/3/A	482	390
	165/70R14	/	85	T	/	R5M	7.2	5.1/2/J	165	628	360/3/A	515	390
	175/65R14	/	86	T	SL	R5M	7.2	6J	177	584	360/3/A	530	390
	175/65R14	/	82	T	/	R5M	7.2	5J	177	584	360/3/A	475	390
	175/65R14	/	88	T	SL	R5M	7.2	5J	177	600	360/3/A	560	390
	175/65R14	/	88	T	/	R5M	7.2	5.1/2/J	177	600	360/3/A	590	390
	185/65R14	/	82	W	/	R5M	7.4	6J	189	578	360/3/A	475	390
	185/65R14	/	86	W	/	R5M	7.4	4.1/2/J	189	596	360/3/A	526	390
	185/70R14	/	88	T	/	R5M	7.4	5J	189	618	360/3/A	590	390
	185/70R14	/	88	W	/	R5M	7.4	5J	189	618	360/3/A	590	390
	185/70R14	/	88	T	/	RW1	7.4	5J	189	618	360/3/A	540	390
	195/65R14	/	86	W	/	R5M	8.0	5J	200	596	360/3/A	536	390
	195/65R14	/	89	W	/	R5M	7.4	5.1/2/J	200	618	360/3/A	586	390
	195/70R14	/	81	T	/	R5M	7.6	5.1/2/J	200	618	360/3/A	615	390
	195/70R14	/	81	T	/	RW1	7.6	6J	200	618	360/3/A	615	390
15	165/60R15	/	77	W	/	R5M	7.2	5J	170	514	360/3/A	412	390

Size: 25.4mm | 20°x0.045mm | 3Dx0.3mm | 35.5mm Load | 31 Load Index | 35 Speed Symbol

HP H11



The specially formulated compounds are **ECO FRIENDLY**, highly fuel efficient and long lasting.



Shoulder Designed

The closed shoulder design strengthens shoulder blocks for superior handling performance.



Wet Performance

The three wide tread grooves and wave-like sipes efficiently drain water to improve grip on wet roads and improve driving safety.

Handling

A pair of center ribs and the solid shoulder blocks maintain stable contact with the road to ensure great handling.

SUMMER

WINTER

ALL SEASON



RIM	SIZE	LOAD INDEX	T.D.	STANDARD RIM	SW	O.D.	MAXLOAD	MAXPRESSURE	UTQG		SIDEWALL
									UTQG	UTQG	
13	145/70R13	71T	--	7	4.508	150	524	345	300	360WA	B/SW
13	145/80R13	75T	--	7	4.008	145	562	387	300	360WA	B/SW
13	155/65R13	73T	--	7.3	4.508	157	532	365	300	360WA	B/SW
13	155/70R13	75T	--	7	4.508	157	548	387	300	360WA	B/SW
13	155/80R13	79T	--	7	4.508	157	578	407	300	360WA	B/SW
13	165/65R13	77T	--	7.2	5.008	170	544	412	300	360WA	B/SW
13	165/70R13	79T	--	7.2	5.008	170	562	407	300	360WA	B/SW
13	165/70R13	83T	XL	7.2	5.008	170	562	407	340	360WA	B/SW
13	165/80R13	83T	--	7.2	4.508	165	564	407	300	360WA	B/SW
13	175/70R13	82T	--	7.2	5.008	177	578	405	300	360WA	B/SW
13	185/70R13	86T	--	7.4	5.508	189	580	530	300	360WA	B/SW
14	155/65R14	75T	--	7	4 1/2J	157	558	387	300	360WA	B/SW
14	165/60R14	75H	--	7.2	5J	170	554	387	300	360WA	B/SW
14	165/65R14	79T	--	7.2	5J	170	570	407	300	360WA	B/SW
14	165/70R14	81T	--	7.2	5J	170	588	402	300	360WA	B/SW
14	165/70R14	85T	XL	7.2	5J	170	588	515	340	360WA	B/SW
14	165/80R14	85T	--	7.2	4 1/2J	165	620	515	300	360WA	B/SW
14	175/65R14	82T	--	7.2	5J	177	584	405	300	360WA	B/SW
14	175/65R14	86T	XL	7.2	5J	177	584	530	340	360WA	B/SW
14	175/70R14	84T	--	7.2	5J	177	602	500	300	360WA	B/SW
14	175/70R14	88T	XL	7.2	5J	177	602	580	340	360WA	B/SW
14	185/60R14	82H	--	7.4	5 1/2J	189	578	405	300	360WA	B/SW
14	185/65R14	86H	--	7.4	5 1/2J	189	586	530	300	360WA	B/SW
14	185/70R14	88H	--	7.4	5 1/2J	189	616	580	300	360WA	B/SW
14	185/70R14	89T	--	7.4	5 1/2J	189	616	580	300	360WA	B/SW
14	195/60R14	86H	--	8	6J	201	590	530	300	360WA	B/SW
14	195/65R14	86H	--	7.4	6J	201	610	580	300	360WA	B/SW
14	195/70R14	91T	--	7.4	6J	201	630	615	300	360WA	B/SW

Load Index | Tire Pressure | Speed Rating | UTQG Load Capacity | UTQG Speed Symbol