

SUMMER | WINTER | ALL SEASON

ROADX
TIRE

T11

SUMMER-HP

A tire specially
MADE FOR TAXIS
to offer low rolling resistance and higher mileage.



T01 is the first choice for both TAXIS AND FAMILY CARS ROADX HP T01

Off-Road

Wider tread and deeper grooves provide excellent endurance and a longer tread life.



Wet Performance

Three main pattern grooves contribute to the tire's efficient water drainage.

Fuel Economy

Outstanding wear-resistant compound and high-strength steel belt reduce rolling resistance for better fuel economy.



FW	SIZE	PR	LI	SR	XL OR NOT	SIDWALL	TD (mm)	STANDARD FEM	S.W. (KFK)	O.D. (mm)	UTQG	MAX.LOAD (kg)	PRESSURE (kPa)
L3	155/65R13	/	73	T	/	GGW	7.5	4.500	157	512	/	305	300
L4	165/60R14	/	75	H	/	BSW	8.0	51	170	518	/	381	300
	165/65R14	/	79	T	/	BSW	8.0	51	170	518	/	451	300
	175/65R14	/	86	T	BL	BSW	8.0	51	177	584	/	536	340
	175/70R14	/	84	T	/	BSW	8.5	51	177	602	/	506	300
	185/60R14	/	82	H	/	BSW	8.5	51/2J	180	518	/	415	300
L5	185/65R14	/	86	H	/	BSW	8.5	51/2J	180	556	/	536	300
	185/60R14	/	86	H	/	BSW	8.5	6J	200	596	/	536	300
	175/60R15	/	75	H	/	BSW	9.0	51/2J	182	567	/	481	300
	185/60R15	/	88	H	BL	BSW	8.5	51/2J	180	603	/	540	340
	185/65R15	/	92	H	BL	BSW	8.5	51/2J	180	621	/	636	340
L6	185/60R15	/	85	V	/	BSW	8.5	6J	200	595	/	515	300
	195/60R15	/	88	V	/	BSW	8.5	6J	200	615	/	560	300
	195/65R15	/	91	V	/	BSW	8.5	6J	200	635	/	615	300
	205/60R15	/	91	V	/	BSW	8.5	6J	200	627	/	615	300
	205/60R13	/	94	V	/	BSW	8.5	6J	180	647	/	615	300
205/55R16	/	94	V	BL	BSW	8.5	6.1/2J	214	632	/	615	340	

Stich-05.4mm 3PR-0.145psi 3RD-0.2.6c XL Extra Load LI Load Index SS Speed Symbol



A tire specially
MADE FOR TAXIS
 to offer low rolling resistance and higher mileage.



■ **Off-Road**

Wider tread and deeper grooves provide excellent endurance and a longer tread life.

■ **Wet Performance**

Three main pattern grooves contribute to the tire's efficient water drainage.

Fuel Economy

Outstanding wear-resistant compound and high-strength steel belt reduce rolling resistance for better fuel economy.



RIM	SIZE	LBS	T.D.	STANDARD RIM		S.W.	O.D.	MAX. LOAD	MAX. PRESSURE	SIDEWALL
				mm	inch					
13	155/65R13	73T	-	7.5	4.50B	157	532	365	300	B3W
14	175/65R14	86T	XL	8	5J	177	584	530	340	B3W
14	175/70R14	84T	-	8.5	5J	177	602	500	300	B3W
14	185/60R14	92H	-	8.5	5 1/2J	189	578	475	300	B3W
14	185/65R14	98H	-	8.5	5 1/2J	189	586	530	300	B3W
14	195/60R14	98H	-	8.5	6J	201	580	530	300	B3W
15	185/60R15	98H	XL	8.5	5 1/2J	189	609	560	340	B3W
15	185/65R15	102H	XL	8.5	5 1/2J	189	621	630	340	B3W
15	195/55R15	85V	-	8.5	6J	201	595	515	300	B3W
15	195/60R15	88V	-	8.5	6J	201	615	560	300	B3W
15	195/65R15	91V	-	8.5	6J	201	635	615	300	B3W
15	205/60R15	91V	-	8.5	6J	209	627	615	300	B3W
15	205/65R15	94V	-	8.5	6J	209	647	670	300	B3W
16	205/55R16	94V	XL	8.5	6 1/2J	214	632	670	340	B3W

Includes: 2.0mm | 100w/214gpl | 190w/230g | 8.0mm Load | 11 Load Index | 85 Speed Symbol